



OMNI™

- Personal Verifier
- Deactivation Verifier
- Portable Deactivator



In developing the OMNI™ tool, Checkpoint designers had three words in mind: *versatile, simple and practical.*

Versatile – The OMNI tool combines three EAS accessories—Personal Tag Verifier (PV), Deactivation Verifier (DV), and Portable Deactivator (PD)—into a single ergonomic package. It eliminates the constant search by Loss Prevention personnel

for the various tools needed to maintain the security system. Instead, they'll find them all contained in the same, easy-to-hold, easy-to-use EAS tool.

Simple – Just set a switch and depress the button. No complicated numbered keypads to program, no more hard-to-reach controls, no more wondering if you're holding the unit properly for the correct operation. The tool's circular target allows for quick, accurate tag location when in Personal Verifier mode.

In Deactivation Verification mode, the OMNI gives a more accurate measure of the deactivation height, resulting in fewer "Failures to Deactivate" at the exits. An optional deactivation key card switches the unit into the Deactivation mode.

When a Portable Deactivator is needed to reduce long customer lines, address incoming alarms or assure a valid purchase, the OMNI handles renegade tags on the spot—eliminating customer wait and embarrassment.

Practical – The self-contained OMNI tool ends the need for constant battery replacement. It utilizes internal batteries that automatically recharge when the unit is placed in its matching docking cradle. And using the docking cradle also ensures that the OMNI tool will always be available when you need it.

Feature Highlights

- The OMNI tool combines three EAS products in a single, easy-to-operate accessory: a Personal Verifier and Deactivation Verifier, with an optional Portable Deactivator mode.
- The OMNI has self-contained, rechargeable batteries—no battery replacement is needed.
- The OMNI has a battery recharger that doubles as its storage cradle. No more lost units—the OMNI is always available right in its cradle, charged and ready to use.
- Deactivation verification accuracy is greatly improved—no more discrepancies between the verifier and actual deactivation height.
- A Deactivator Key turns the OMNI tool into a Portable Deactivator, perfect for reducing customer wait times through on-the-spot "live" tag deactivation and in remote cashier applications.



OMNI™

- Personal Verifier
- Deactivation Verifier
- Portable Deactivator



Optional Deactivator Key

Specifications:

OMNI:

Dimensions: 16" (406mm) Long x 2.25" (57mm) High x 6.5" (165mm) Diameter
Light gray high-impact plastic, molded through color

Weight: 1.2 lb. (.55kg)

Power Supply:

Universal power supply allows for worldwide use

Deactivation Key Card Option:

Dimensions: 2.125" (54mm) Wide x 3.375" (86mm) High x .062" (1mm) Thick
(Kit with deactivation key card may be purchased as an optional item)

Docking Cradle:

Dimensions: 4.5" (114mm) Wide x 3" (76mm) High x 1" (25mm) Deep

Frequencies Detected:

Primary Frequencies: 7.8, 8.2, 8.6, 9.0, or 9.5 MHz

Secondary Frequencies: 1.8, 2.0, 2.2, 3.25, 4.75, 5.0, 5.5, or 16.5 MHz



LED indicates operational mode



Checkpoint Systems, Inc.
101 Wolf Drive, P.O. Box 188
Thorofare, NJ 08086
800 257 5540 Toll Free
856 848 1800 Phone
856 848 0937 Fax
www.checkpointsystems.com